

# L'ANTIC COLONIAL

**Model:** JAVEA GRIS 20X20(A)

**Size:** 20 x 20 cm

**Thickness:** 9 mm

**Code:** 100057616 · L132300041

**Water absorption group :** BIII - Wall tiles ( $10\% \leq E \leq 20\%$ )

Standard: ISO-13006:1998 y UNE EN 14411:2007



DAPc.002.008  
DECLARACIÓN AMBIENTAL  
DE PRODUCTO DE LA CONSTRUCCIÓN  
<http://es.csostenible.net/dapc>



## DIMENSIONAL FEATURES

Standard: UNE-EN ISO 10545-2



**Production size:** 200 x 200 mm

**Length and width deviation:** Below 0.2%

( $\leq 0.5\%$ )\*

**Side straightness deviation:** Below 0.2%

( $\leq 0.5\%$ )\*

**Squareness deviation:** Below 0.2%

( $\leq 0.6\%$ )\*

**Surface flatness deviation:** Below 0.2%

( $\leq 0.5\%$ )\*

\*ISO-13006:1998 UNE-EN 14411:2007

## MECHANICAL FEATURES

Standard: UNE-EN ISO 10545-4-6-7-11



**Breaking strength and modulus of rupture:** - -

( $\geq 600$  N)\* ( $\geq 12$  N/mm<sup>2</sup>)\*

**Abrasion resistance:** -

**Crazing resistance:** Resists 3 cycles.

\*ISO-13006:1998 UNE-EN 14411:2007

## HYGIENIC FEATURES

Standard: UNE-EN ISO 10545-13-14:1995



**Chemical resistance:** Class "A" for swimming pools and cleaning products (resists attack).

Minimum Class "B" for acids and bases.

(CLASE B Min.)\*

**Stain resistance:** Class 5. Easy cleaning with water.

(CLASE 3 Min.)\*

\*ISO-13006:1998 UNE-EN 14411:2007

## SCOPE OF USE

1: Hygienic.

Do not use cleaning agents containing hydrofluoric acid.

It is recommended to fix tiles with a minimum joint of 1,5 mm. Do not fix without joint.

For big sizes, it is recommended to fix with mortars containing polymeric additives and to use the double glueing technique.

Mosaic tiles must be grouted.

This document is only commercial and cannot be used as expert opinion, documentary evidence or in any legal or administrative procedure unless authorized by PORCELANOSA S.A.

CERTIFICATION SYSTEM

